



# COMPACT HYDRAULIC BRAKE PACKAGES FROM TWIFLEX PROVIDE SINGLE-SOURCE CONVENIENCE FOR A WIDE RANGE OF INDUSTRIAL APPLICATIONS

A variety of standard and custom hydraulic brake packages are available from Twiflex to meet the static holding and dynamic (emergency) stopping duty requirements of many types of applications including elevators, ship loading gantry cranes, escalators, metal mill ladle cover hoists, amusement rides, conveyors, cold steel mills, ski lifts, and more.

Twiflex brake packages combine world-class Twiflex spring applied, hydraulically released caliper brakes with the state-of-the-art LCS hydraulic power unit mounted on a custom fabricated base/pedestal. These compact units feature a small footprint allowing them to fit into applications with limited space available.

Complete, ready-to-install brake assemblies from Twiflex provide time-saving convenience to OEMs while ensuring component compatibility and optimized performance.

### **Advanced LCS Hydraulic Power Unit**

The Twiflex Type LCS is a compact hydraulic power unit designed to operate small caliper brakes in a proven, reliable package.

It provides on/off control of the spring applied ("passive") brakes, with a selectable "fast-approach/soft-braking" function integrated into the circuit as standard. This feature rapidly brings the brakes onto a factory-set touch pressure (pads in contact with the disc face) before the remaining pressure decays to zero and the brakes gradually apply.

A wide range of motor and auxiliary connection voltages can be accommodated. A terminal box permits the addition of a motor contactor if preferred. A hand-pump assembly allows manual release of the calipers in the event of complete power loss.

### **Specifications:**

• Motor: 0.9 kW, 480 VAC, 60 Hz

Pump: 1.6 CC/REV
Solenoid Coils: 24 VDC
Pressure Switch: 24 VDC
Wired to Terminal Box



# **Superior Caliper Disc Brake Technologies**

Industry-leading Twiflex spring applied, hydraulically released caliper brake technologies are the core of these assemblies. Reliable Twiflex brakes are designed and built for long lasting, trouble-free performance.

All brakes feature:

- Modular construction for easy maintenance
  - Low pad pressures
  - Easy set up and adjustment

www.twiflex.com P-8454-TF 5/18




# STANDARD TWIFLEX BRAKE PACKAGES

Twiflex standard brake packages are available with three different spring applied, hydraulically released brake models with braking force ratings ranging from 6.8 kN to 119 kN. These compact configurations are designed to meet the most common range of application requirements. All three packages are shipped complete with a hand pump, terminal box, and pressure gauge.

# **All Standard Packages Include:**

- Brake Assembly (spring applied, hydraulically released)
- LCS Hydraulic Power Unit
- Mounting Base/Pedestal
- Hand Pump (including manual detents)
- Terminal Box
- Pressure Gauge (0-250 bar)



# **Dimensions (mm)**

Model	A	В	С
MXSH	412	609.5	895
VCS	404	699.5	985
VKSD	676	749.5	1035
GMRSH	426	680.5	966

Height: 750mm to top of handle



Standard MXSH Disc Brake Caliper Package

**Maximum Braking Force:** 14.3 kN (3,215 lbf)



Standard GMRSH Disc Brake Caliper Package

**Maximum Braking Force:** 36 kN (8,093 lbf)



Standard VCS Disc Brake Caliper Package

**Maximum Braking Force:** 62 kN (13,938 lbf)



Standard VKSD Disc Brake Caliper Package

**Maximum Braking Force:** 119 kN (26,752 lbf)

# CUSTOM ENGINEERED BRAKE PACKAGES

Twiflex engineers routinely configure custom brake package solutions to meet individual OEM specifications. A range of Twiflex spring applied, hydraulically released brake models can be incorporated into the design to achieve specific braking requirements. Certain size dual brake configurations can be utilized for higher braking torque applications.

Standard and custom discs/rotors (with or without hubs) as well as sensors can be included in application packages as needed.



#### **Twiflex Facilities**

#### **Europe**

### **United Kingdom**

9 Briar Road, Twickenham Middlesex TW2 6RB - England +44 (0) 20 8894 1161 info@twiflex.com sales@twiflex.com

Caliper Brakes and Thrusters

Ampthill Road Bedford, MK42 9RD - UK +44 (0)1234 350311 Caliper Brakes and Thrusters

#### Germany

Hatschekstraße 36 69126 Heidelberg - Germany +49 (0) 6221-30470 Caliper Brakes and Thrusters

#### **North America**

2800 Fisher Road Wichita Falls, TX 76302 - USA 940-723-3483 Toll free: 844-723-3483 twiflex.info@twiflex.com

Caliper Brakes and Thrusters

#### **Asia Pacific**

#### Australia

+61 2 9894 0133

#### China

+86 21 5169-9255

#### Hong Kong

+852 2615 9313

#### Singapore

+65 6487 4464

#### Taiwan

+886 2 2577 8156

#### Thailand

+66 2322 5527

### The Brands of Altra Industrial Motion

#### **Couplings**

Ameridrives www.ameridrives.com

#### Bibby Turboflex

www.bibbyturboflex.com

#### **Guardian Couplings**

www.guardiancouplings.com

#### Huco

www.huco.com

#### **Lamiflex Couplings** www.lamiflexcouplings.com

Stromag

#### www.stromag.com TB Wood's

www.thwoods.com

#### **Geared Cam Limit Switches**

# Stromag

www.stromag.com

#### **Electric Clutches & Brakes**

Inertia Dynamics

#### Matrix

www.matrix-international.com

#### Stromag

www.stromag.com

# Warner Electric

www.warnerelectric.com

#### **Linear Products**

**Warner Linear** www.warnerlinear.com

#### **Engineered Bearing Assemblies**

www.kilianbearings.com

### **Heavy Duty Clutches & Brakes**

#### Industrial Clutch www.indclutch.com

# Twiflex

www.twiflex.com

# Stromag

www.stromag.com

# Svendborg Brakes www.svendborg-brakes.com

Wichita Clutch

#### www.wichitaclutch.com

#### **Belted Drives**

TB Wood's www.tbwoods.com

#### Gearing

#### **Bauer Gear Motor** www.bauergears.com

# **Boston Gear**

# www.bostongear.com

# **Delroyd Worm Gear**

**Nuttall Gear** 

### www.nuttallgear.com

# **Overrunning Clutches**

# **Formsprag Clutch**

### **Marland Clutch**

#### Stieber

www.stieberclutch.com

Neither the accuracy nor completeness of the information contained in this publication is guaranteed by the company and may be subject to change in its sole discretion. The operating and performance characteristics of these products may vary depending on the application, installation, operating conditions and environmental factors. The company's terms and conditions of sale can be viewed at http://www.altramotion.com/terms-and-conditions/sales-terms-and-conditions. These terms and conditions apply to any person who may buy, acquire or use a product referred to herein, including any person who buys from a licensed distributor of these branded products.

©2018 by Twiflex LLC. All rights reserved. All trademarks in this publication are the sole and exclusive property of Twiflex LLC or one of its affiliated companies.



www.twiflex.com P-8454-TF 5/18